

Tank & Vessel Weighing











ITA Integrated Tank Assembly

Tank Weighing Assemblies

Innovative design, and tough construction define GSE Tank Weighing Assemblies. They offer operational safety, quick installation, overload protection, and steelwork misalignment tolerance. Stainless steel, hermetically sealed load cells are available.





ITA Integrated Tank Assembly Shown with conduit fitting

ITA Integrated Tank Assembly Shown with stainless steel base plate and captive cable

Specifications

PERFORMANCE	ITA Integrated Tank Assembly
Capacities (lb)	Medium Duty: 1000 lb—125,000 lb (454 kg—56,699 kg)
Rated Output	3 mV/V ± 0.10 %
Non-linearity of Rated Output	± 0.05 %
Non-repeatability of Rated	± 0.05 %
Output	± 0.03 %
Creep (30 minutes)	± 0.03 %
Temp Effect on Zero Balance	± 0.0015 % / °C
Temp Effect on Span	± 0.0008 % / °C
Compensated Temp Range	10 °F to 110 °F (-12 °C to 43 °C)
Operating Temp Range	10 °F to 110 °F (-12 °C to 43 °C)
Safe Overload F.S.	150 %
Ultimate Overload F.S.	300 %
Input Resistance / Impedance	350 ± 3 Ω*
Output Resistance / Impedance	$350 \pm 3 \Omega^*$
ELECTRICAL/WIRING	ITA Integrated Tank Assembly
Excitation Voltage	10-15 VAC/VDC
Cable Length	25 ft (7.62 m)
Excitation +	Green
Excitation –	Black
Signal +	White
Signal –	Red
CONSTRUCTION	ITA Integrated Tank Assembly
Material	Load Cell: Stainless Steel Hermetically Sealed NEMA 4X (IP66/ IP68) Cable Exit: Conduit fittings or captive cable Hermetic Connector: Optional Base Plate: Stainless Steel
Dimensions	1000-10,000 1.37 in x 4.5 in (34.8 mm x 114.3 mm) 15,000 1.62 in x 4.5 in (41.2 mm x 114.3 mm) 20,000-50,000 2.53 in x 7.0 in (67.31 mm x 177.8 mm) 60,000-125,000 3.12 in x 8.0 in [79.25 mm x 203.2 mm]

^{*}Nominal

ITA Integrated Tank Assembly

The ITA is an innovative self-contained low profile weighing assembly with an integrated load cell and mounting assembly. The ITA design allows up to 3° off its axis without affecting weighing accuracy. The durable, stainless steel welded construction prevents intrusion from moisture or chemicals; providing years of service in the most severe environments. Integral to the ITA design is its uplift restraint and side load protection; eliminating the need for check rods or stabilizing hardware in most applications.


FEATURES

ITA Medium Capacity: 1000 lb-125,000 lb (454 kg-56,699 kg)

- Stainless steel base plate (medium capacity only)
- Low profile, self-checking
- Integrated load cell and mount
- NEMA 4X (IP66/IP68) Ingression Rating



ITA Integrated Tank Assembly



AUTHORIZED DISTRIBUTOR



888-236-5650 sales@bsiscales.com www.bsiscales.com

www.averyweigh-tronix.com

Avery Weigh-Tronix



Avery Weigh-Tronix is an ITW company